



# Bag Adaptor LL

## TECHNICAL DATASHEET

The Chemfort™ Bag Adaptor LL (Luer Lock) connects between a standard IV bag or semi rigid container to any (gravity or pump) IV administration set with a female luer lock connector. After spiking and priming the set, a safe drug transfer from the syringe into the IV bag or semi rigid container is installed through a closed connection with the Chemfort™ Syringe Adaptor/Syringe Adaptor Lock. A “click” sound indicates a safe connection between two Chemfort™ components. A simple pinch on the SA/SAL wings will disconnect it from the Bag Adaptor LL. The self-sealing elastomers prevent drug leakage and droplet formation on the outer septa surfaces. The Chemfort™ portfolio has no known incompatibilities with hazardous drug solvents.

### Indications for Use:

Chemfort™ is a Closed System Transfer Device (CSTD) that mechanically prohibits the release of drugs, including antineoplastic and hazardous drugs, in vapor, aerosol, or liquid form during preparation, reconstitution, compounding and administration, minimizing exposure of individuals, healthcare personnel and the environment to hazardous drugs. Chemfort™ prevents the introduction of microbial and airborne contaminants into the drug or fluid path for up to 7 days.

### TECHNICAL DATASHEET

#### Order information

Article number / Reference	MG245249
User box quantity	40 pcs
Transport box quantity	80 pcs

#### Product Characteristics

##### Product technical data

Tubing length	40 cm
Volume of the tubing	2.80 ml
Spike type	Non-vented 2-way spike
Distal end of the tubing	Male luer lock connection with flow-stop protection cap
Clamp type	Pinch clamp
Septum piercings	Up to ten times
Shelf life	3 years
Sterilization	Ethylene Oxide

Tolerates disinfection with alcohol 70% and chlorhexidine in alcohol (5 mg/70% alcohol)

#### Material Specifications

Component	Material
Protective cap on spike	Polyethylene
2-way Spike	PET
Elastomeric sealing	Polyisoprene
Soft tubing	PVC-DEHP free
Pinch clamp on tubing	Acetal
Male luer lock body and collar on distal end of tubing	ABS
FlowStop protection cap	P.E.H.D and Acrylic copolymer membrane (hydrophobic)

PVC-DEHP free. Non-pyrogenic. Free from latex, lead, cadmium, arsenic and chrome. Meets standards and regulations with regards to the environment.

#### Regulation

##### CE 0483

Disposal of components should be according to local regulations and procedures for handling of hazardous drugs

Symbols taken from ISO 15223-1:2016



Sterilized using ethylene oxide



Non-pyrogenic



Do not re-sterilize



Do not re-use



Do not use if package is damaged



Keep dry



Keep away from sunlight



Donawa Lifescience Consulting Srl  
Piazza Albania 10,  
00153 Rome, Italy

CE 0483

**SIMPLIVIA™**

Simplivia Healthcare Ltd.  
North Industrial Zone  
P.O. Box 888  
Kiryat Shmona, Israel 1101801



www.simplivia.com



info@simplivia.com



Follow us